

BEST AVAILABLE COPY

(12) UK Patent Application (19) GB (11) 2 211 691 A (13)

(43) Date of A publication 05.07.1989

(21) Application No. 8825273.9

(22) Date of filing 28.10.1988

(30) Priority data

(31) 62270186
6369366

(32) 28.10.1987
25.03.1988

(33) JP

(51) INT CL*

H04N 7/133

(52) UK CL (Edition J)

H4F FD1B1 FD1D1 FD12X FD3 FD30B FD30K
FD30X FD31G FD31K FD31M FRW

(56) Documents cited

None

(58) Field of search

UK CL (Edition J) H4F FESA FESG FESK FESX
FRQ FRT FRW
INT CL* H04N

(71) Applicant
Hitachi Ltd

(Incorporated in Japan)

6 Kanda Surugadai 4-chome, Chiyoda-ku, Tokyo,
Japan

(72) Inventors

Yuuji Iizawa
Junichi Kimura
Masaki Takizawa

(74) Agent and/or Address for Service

Mowburn Ellis
2 Cursitor Street, London, EC4A 1BQ, United Kingdom

(54) Picture coding and interpolation apparatus

(57) A picture coding apparatus operates on blocks of pixels with an orthogonal matrix transformation, 4, to generate data a the frequency content of the block, and subsequently reduces the redundancy of the data by quantisation, 6, and entropy encoding such as variable-length encoding. Additional manipulation of the picture signal, such as expansion, compression, rotation, filtering etc is achieved by multiplying the orthogonal transform matrix with another matrix within coefficients memory 5, prior to operation on the signal.

Motion compensation may be employed (Fig 3).

Also described (Fig 5) is an interpolation arrangement wherein the orthogonal matrix transformation (e.g. Discrete Cosine Transformation) is followed by an interpolation matrix transformation so as to change the number of pixels. These two matrices may be combined so that a single transformation is applied to the signal.




FIG. 1

GB 2 211 691 A